



Speedshine 400SP

Precision engineered

Ideal for buffing, spray burnishing and stripping polish off floors.

This machine is also designed for tough sanding jobs on wooden floors. The Speedshine 400SP Suction Polisher has a true center mount drive motor with a double reduction gearbox, this offers a balanced ease of use, that leaves the operator in control. The vacuum system is fully enclosed and mounted on the base of the machine to improve performance and eliminates weight on the handle that loads the operator. .

Quality is built into all the components:

Including stainless steel handle, axle and all fasteners. The motor has a fin aluminum chassis that allows for the coolest running motor on the market. The engineering shows through with the quietness of the double reduction gearbox.

The gearbox does not require maintenance or adjustments.

The vacuum system is fully enclosed so dust does not escape as in bag fill machines and no debris passes through the fan that can cause damage and bearing wear. Designed with a tough plastic cover that protects the motor and components, like the capacitors. It also keeps the machine looking good with its clean lines and durability



Clever and practical

Rotobic



1) Sealed vacuum system with optional disposable dust bags. A clear lid for the operator to see if the bag is full.

2) Ergonomic design: With control handle and grips. Made safe, flame retardant plastic materials.

3) The skirt is fixed to the underside of the bumper Ensures the skirt does not pull off accidentally. Increasing productivity

4) Ergonomic switch levers. Allow the load to be spread over the whole hand. The vac switch is located for ease of use.

5) Quick Release pad drive/brush hub. Stainless Steel under body plate. 45cm brush or pad drive, for greater peripheral speed for a better result.

6) Robust injection molded cover. Improves cooling and protects the motor. Prevents dents and scratches.

7) Cam lever locks the handle with ease for Operator comfort.

8) 200 mm double ball Bearing wheels for easy transport. The wheels are non marking and rated at 400Kgs

Technical data	Description
Motor	850W 2 stage fan Flow-thru
Filtration	4 stage filtration 99.98% at 0.3 micron
Vacuum	Thermal cut-out
Brush Speed Brush	386 RPM, 45cm
Lead	15M Heavy Duty, Rubber with cable restraint
Size Vacuum System	Fully sealed canister with optional disposable bags. Clear lid.
Filtration	4 stage filtration 99.98% at 0.3 micron
Filter bag capacity	2.8L
Handle	Fully Adjustable
Wheels	200mm double bearing, rated 400Kgs
Gearbox	Double reduction, helical gears Maintenance Free
Weight	40 kg

Optional disposable dust bags

Make disposing of collected dust clean and easy



Motor and Gearbox Assembly



Hako Australia Pty Ltd
www.hakoaustralia.com.au
 hksales@hakoaustralia.com.au
 Phone: 1800 257 221